

MANUAL OF CONTRACT DOCUMENTS FOR HIGHWAY WORKS
VOLUME 1 SPECIFICATION FOR HIGHWAY WORKS

**SERIES 1200
TRAFFIC SIGNS**

Contents

Clause	Title	Page
# 1201	Regulations, Sign Classification and Standards	2
1202	General Requirements for Permanent Traffic Signs	2
1203	Foundations for Permanent Traffic Signs and Signals	3
1204	Posts for Permanent Traffic Signs	3
1205	Sign Plates for Permanent Traffic Signs	3
1206	Faces for Permanent Traffic Signs	4
1207	Construction and Assembly of Permanent Traffic Signs	4
1208	Location and Erection of Permanent Traffic Signs	5
1209	Covering of Permanent Traffic Signs	5
1210	Permanent Bollards	6
1211	Permanent Marker Posts	6
# 1212	Road Markings	6
# 1213	Road Studs	9
1214	Traffic Cones, Traffic Cylinders, Flat Traffic Delineators and Other Traffic Delineators	8
1215	Road Danger Lamps and High Intensity Flashing Beacons	11
1216	Temporary Traffic Signs	11
1217	Traffic Signals	13
1218	Detector Loops	14
1219	Controlled and Un-controlled Crossings	14
1220	Traffic Signs on Gantries	14
1221	Preparation and Finish of Metal and Other Surfaces	14

**NATIONAL ALTERATIONS OF THE
OVERSEEING ORGANISATIONS OF
SCOTLAND, WALES AND NORTHERN
IRELAND**

Wales

1201WO	Regulations, Sign Classification and Standards	W1
--------	--	----

Northern Ireland

1201NI	Regulations, Sign Classification and Standards	N1
1212NI	Road Markings	N1
1213NI	Road Studs	N3

denotes a Clause which has a substitute National Clause for one or more of the Overseeing Organisations of Scotland, Wales or Northern Ireland.

TRAFFIC SIGNS

#1201 Regulations, Sign Classification and Standards

Regulations

1 Subject to paragraphs 2 and 3 below, all traffic signs used (including reflectors and road markings), whether permanent or temporary, shall be of the size, shape, colour and type prescribed for that use in the Traffic Signs Regulations and General Directions (Statutory Instrument No. 1519 1994), including Working Drawings for Traffic Sign Design and Manufacture (Volumes 1, 2 and 3), the Zebra, Pelican and Puffin Pedestrian Crossings Regulations and General Directions (Statutory Instrument No. 2400 1997) and subsequent amending Regulations. Other relevant requirements are contained in the above Regulations and General Directions.

2 Signs that are not prescribed in Regulations need to be specially authorised by the Secretary of State. Where the Contractor proposes to use non-prescribed temporary traffic signs, he shall obtain the agreement of the Overseeing Organisation to their intended design and location. Where the Contractor proposes to use prescribed temporary traffic signs, he shall obtain the agreement of the police and the highway authority to their intended location. The Contractor shall obtain authorisation and approval from the Overseeing Organisation for the use of the signs at the specific locations proposed.

3 Signs that are changeable by means other than the purely mechanical require statutory type approval for their construction and operating mechanisms by the Secretary of State. This requirement is in addition to the need for the design of the sign to be prescribed or specially authorised. The Contractor's proposal for signs that require statutory type approval shall include the reference numbers of any approval already issued in respect of that equipment. The signs shall not be installed until appropriate approval or confirmation of existing approval, by the Overseeing Organisation has been obtained.

Sign Classification

4 For the purposes of the Contract the following classifications apply:

- (i) permanent traffic signs. Any of the traffic signs prescribed in the Regulations, or

specially authorised by the Secretary of State, or any part thereof, designed to remain in position at the completion of the Permanent Works or a traffic cone, cylinder or other traffic delineator to be retained by the Employer;

- (ii) prescribed temporary traffic signs. Any of the traffic signs defined in the Regulations, or specially authorised by the Secretary of State, or any part thereof, described in Appendix 12/1 which, unless otherwise described in Appendix 12/1, comply with the requirements of a permanent traffic sign but which will not remain in position at the completion of the Permanent Works;

- (iii) temporary traffic signs. Any of the traffic signs defined in the Regulations, or specially authorised by the Secretary of State, or any part thereof, designed by the Contractor, in compliance with Clause 1216 which will not remain in position at the completion of the Permanent Works.

Standards

5 Traffic signs shall comply with BS 873 : Parts 1 to 8 unless otherwise stated.

1202 General Requirements for Permanent Traffic Signs

1 Materials for permanent traffic signs and their construction, assembly, location and erection shall comply with this Series, the 1400 Series and the requirements described in Appendix 12/1.

2 Each complete traffic sign or part thereof shall be capable of passing the tests in BS 873 : Part 1.

3 Sign panels of internally illuminated signs and luminaire face panels shall, unless otherwise described in Appendix 12/1, comply with impact Category 1 of BS 873 : Part 5.

4 All lit traffic signs shall comply with Category 1 luminance of BS 873 : Part 5 unless otherwise described in Appendix 12/1.

5 Before the commencement of fabrication of any traffic sign, unless otherwise stated in Appendix 12/1, the Contractor shall submit for the Overseeing

Organisation's approval:

- (i) fabrication drawings for 'directional informatory' and 'informatory' signs as required in Appendix 1/4;
- (ii) the information about 'warning', 'regulatory' and other traffic signs required in Appendix 12/1.

6 All traffic sign housings shall be provided with vandal and weather resistant locks. Keys, in the quantities stated in Appendix 12/1, shall be provided to the Overseeing Organisation. Types of lock shall be kept to a minimum.

7 The backs of traffic signs shall have a location identifying mark as described in Appendix 12/1.

8 Traffic signs shall be carefully handled to prevent damage, transported and stored in accordance with the sign face manufacturer's instructions.

1203 Foundations for Permanent Traffic Signs and Signals

1 The type and size of foundations for permanent traffic signs and signals shall be as described in Appendix 12/1 and, unless otherwise stated therein, shall comply with this Clause.

2 All excavations for foundations shall be carried out in compliance with Clause 604 and shall be cleared of all loose material before placing of concrete and backfilling.

3 Unless otherwise described in Appendix 12/1 traffic signs and signals supported by a single post placed in the ground shall have the post installed centrally in 300 mm diameter or square holes filled in compliance with Clause 2602 with mix ST2 concrete to within 150 mm of the ground surface.

4 Unless otherwise described in Appendix 12/1, posts shall be supported for a minimum of three days after placing the concrete and backfilling shall not take place until at least 48 hours after placing.

5 For traffic signals and illuminated signs provision shall be made for cable entry through the foundation by means of ducting as described in Appendix 12/1.

6 Where pockets are formed in concrete foundations their plan dimensions shall be sufficiently larger than those of the post to allow for positioning and bedding of the post and backfilling of the pocket.

7 All backfilling of foundations shall comply with Clause 611 except that where pipes or buried cables are installed it shall comply with Clauses 505 and 1421 respectively.

8 Reinstatement of existing surfaces above foundations shall comply with Clause 706.

1204 Posts for Permanent Traffic Signs

1 Posts for permanent traffic signs shall be as described in Appendix 12/1 and shall comply with BS 873 : Part 7, the surface protection requirements of BS 873 : Part 6 and with the following:

- (i) steel posts shall be tubular or rectangular hollow section complying with BS EN 10210, joists, universal beams or columns complying with BS 4, and shall be manufactured from steel complying with grade S275JO or S275J2;
- (ii) aluminium posts shall be of tubular or rectangular hollow section;
- (iii) concrete for reinforced or prestressed concrete posts shall comply with the 1700 Series and Appendix 12/1.

2 Posts shall not protrude above the top of the sign unless supporting an external luminaire, in which case the protrusion shall be kept to a minimum.

3 Internally illuminated posts for pedestrian crossing beacons shall comply with this Clause and where appropriate with BS 873 : Part 7.

4 Signs erected on a single post shall be positioned so that the post is in the centre of the sign, unless otherwise described in Appendix 12/1.

5 Compartments for electrical equipment shall be as described in Appendix 12/1 and, wherever practicable, access doors shall be on the side of the compartment furthest from approaching traffic. In the case of signs supported by more than one post, such compartment shall be on the post furthest from the carriageway unless otherwise described in Appendix 12/1.

6 Flange plates shall have holes or slots as described in Appendix 12/1 to accommodate the attachment system.

1205 Sign Plates for Permanent Traffic Signs

1 All permanent sign plates shall comply with BS 873 : Part 6, and with this Clause.

2 Plate signs not exceeding 1.2 m in height and 2.4 m width shall be made of a single sheet. Where more than one sheet is used to make up a sign, the number of sheets shall be kept to a reasonable minimum and the separate sheets shall be rectangular and of comparable size and shape.

3 Extruded plank signs up to 4.8 m wide shall have no vertical joints. Above this size, joints in extruded planks should preferably be positioned at a vertical support; if not, then the vertical joints in adjacent planks should not be less than 1.0 m apart and only one joint per extruded plank is permitted.

4 Fabricated plank signs up to 4.8 m wide shall have no vertical joints, but each plank may be constructed from a maximum of two pieces of sub-strate material, producing one split line. Split lines should be lined up vertically or horizontally. Above 4.8 m wide, joints in the stiffening extrusions of adjacent planks should preferably be positioned at a vertical support; if not, then the vertical joints in the stiffening extrusions of adjacent planks should not be less than 1.0 m apart and only one such joint per fabricated plank shall then be permitted.

5 Where top and bottom light spill screens are required in Appendix 12/1, these shall extend for the whole width of the sign and be fabricated out of the same material as the sign plate.

6 Top and bottom light spill screens shall be considered as part of the sign plate and any stiffeners and mounting fittings shall be designed to accommodate the combined size.

1206 Faces for Permanent Traffic Signs

1 Faces for permanent traffic signs shall be as described in Appendix 12/1. They shall comply with BS 873 : Part 6 and with this Clause.

2 All plastics sheeting shall be fixed in accordance with the sheeting manufacturer's instructions.

3 Only vertical and horizontal joints shall be permitted and all joints in plastics sheeting shall be overlapped by not less than 6 mm. The overlap in the horizontal joints shall be from the top. Butt joints in plastics sheeting shall not be used, except between individual planks or in electro cutable overlay film, or as recommended by the sheeting manufacturer.

4 All materials comprising the sign face, including the background, border and legends shall be carefully matched for colour at the time of sign fabrication to provide uniform appearance both by day and night. The sheeting manufacturer's recommendations on colour matching methods shall be observed.

5 Letters, numerals, symbols and borders shall be clear cut, sharp edged and without cracks.

6 Any cut-out letters, numerals, symbols and borders shall be of material compatible with the sheeting to which they are applied. They shall be applied in

accordance with the sheeting manufacturer's instructions.

7 Screen processed letters, numerals, symbols and borders shall be screen printed with materials in accordance with the sheeting manufacturer's instructions. Any inks, pastes and finishing coats used shall be compatible with the sheeting material or the face panel of internally illuminated signs.

8 Sheeting materials including letters, numerals, symbols and borders shall be fully adhered and there shall be no air bubbles, creases, cracks or other blemishes. Where the sheeting manufacturer requires the assembled materials to be provided with a coat of clear lacquer, it shall be uniform and continuous. All lacquer shall be applied at the time of fabrication of the sign face and shall be of a type specified or supplied by the sheeting manufacturer.

1207 Construction and Assembly of Permanent Traffic Signs

General

1 Construction and assembly of traffic signs shall comply with BS 873 : Part 6 and with this Clause.

2 All sign plates and planks, frames, purlins, posts and other components shall be de-burred prior to assembly.

3 Where framing and stiffening are not an integral part of the sign plate their joints shall be welded or joined with suitable brackets utilising nuts, bolts and washers.

4 Where purlins are adopted they shall be attached to each vertical member of the sign frame and the sign stiffening and framing shall be continuous in the vertical direction. Purlins shall be spaced equally apart. Connections shall be made at every point where a purlin crosses a post.

5 Where purlins are not adopted the sign stiffening and framing shall be continuous in the horizontal direction.

6 Rivets and other devices used for fixing sheet sign plates to their stiffeners or framework, or in the construction of housings, shall be of a material compatible with the materials being joined. Spacing of rivets or other fixing devices shall be uniform and shall not exceed 150 mm around the outside edge of any sheet or section of sheet, and shall not exceed 300 mm on cross braces. Hollow rivets shall not be used. Where sign plates need to be stiffened this shall be achieved in a manner such that the sign face material is not punctured or otherwise damaged to accommodate the stiffening.

7 An additional washer of neoprene, nylon or other suitable material shall be used between the sign face and any metal nuts, bolts, washers and screws to protect it from corrosive or other damaging effects.

8 Where supports to traffic signs, including external lighting luminaires, are required to have flange plates these shall be secured by anchorages and attachment systems complying with the 1300 Series. The bolts shall be lightly greased before final installation and they and their anchorages shall be installed so as to achieve the loadings, torque settings and other requirements described in Appendix 12/1.

9 Sheet and plank signs shall be connected to posts by an appropriate method. Banding systems shall be of stainless steel complying with AISI Grade 201.

10 Plank signs shall be assembled in accordance with the manufacturer's instructions.

11 Where ferrous components are permitted any drilling of them shall be completed before the application of any finish.

12 Any hole drilled in plates with plastics sheeting to accommodate a rivet or bolt shall immediately prior to the insertion of the rivet or bolt have a clear lacquer, recommended by the plastics sheeting manufacturer, applied to its edge to prevent the ingress of moisture. The surfaces of rivets or bolts exposed on the sign face shall be covered by a suitable material of a colour to match that part of the face.

13 Prior to fitting any sign to any lighting column, the Contractor shall ensure that the sign is included in the technical approval of the lighting column in accordance with Standards BD 2 and BD 26. No holes shall be drilled in the lighting column except those whose location and size are included in the technical approval.

14 Traffic signs to be erected on road lighting columns shall have fixings compatible with the column cross-section and finish. Wiring shall be contained in external conduit complying with BS 4568. Conduits shall be affixed to concrete lighting columns with stainless steel banding systems complying with AISI Grade 201. Conduits shall be affixed to other lighting columns with stainless steel clamps which shall be screwed with stainless steel screws into tapped holes in the lighting column. Alternatively permanent cabling shall be placed on the inside of the lighting column and shall exit via a bushed drilled hole.

Variable Message Traffic Signs

15 Variable message traffic signs shall comply with this Clause.

1208 Location and Erection of Permanent Traffic Signs

1 The approximate location of each traffic sign is described in Appendix 12/1. All traffic signs shall have their exact location determined and recorded in compliance with Clause 1403.

2 All posts shall be erected plumb and where two or more posts are provided for any one sign, the faces of the posts shall be lined up.

3 Signs erected on two posts shall have each post positioned so that the distance from the centre of the post to the edge of the sign plate is 300 mm unless otherwise described in Appendix 12/1.

4 Any pockets formed in concrete foundations to receive the posts shall be cleaned out immediately prior to erection. The posts shall be placed centrally in the pockets and be bedded on mortar designation (i) complying with Clause 2404 and, unless otherwise described in Appendix 12/1, the pockets shall be filled up to finished foundation level with mix ST5 concrete.

5 Traffic signs mounted on posts, except those on gantries, shall be erected to have their face plumb and be orientated in relation to the carriageway in accordance with Chapter 1 of the Traffic Signs Manual.

6 Traffic signs mounted on gantries shall be erected as described in Appendix 12/6 and all other traffic signs shall be erected as described in Appendix 12/1.

7 The site records required by Clause 1402, shall include daily records for non-lit traffic signs.

8 No traffic sign shall be dismantled, resited or removed without the prior approval of the Overseeing Organisation.

1209 Covering of Permanent Traffic Signs

1 Where it is required in Appendix 12/1 that permanent traffic signs be blanked-out or have an alternative message, the method to be adopted shall comply with the following, unless otherwise described in Appendix 12/1:

- (i) for plate signs: A cover plate compatible with the plate sign's material, or a covering of a suitable, opaque, non damaging material, or, for covering periods of up to one year, a self adhesive plastic film to support the temporary sign face sheeting;
- (ii) for other traffic signs: A covering of a suitable, opaque, non damaging material.

2 Cover plates shall be suitably fixed to give a 10 mm minimum air gap between the sign face and cover plate. The fixing method shall not cause damage

or staining to the sign face. Any holes remaining in the finished sign face after removal of the plate shall be filled with a suitable material, of a colour to match that part of the face.

3 Where self adhesive plastic film is used it shall be compatible with the sign face materials and be applied and removed in compliance with the manufacturer's instructions.

4 Any loose covering used must be sufficiently opaque to prevent reflection from and legibility of the covered sign and be securely fastened to the back of the sign. Under no circumstances shall tape or other adhesive material be applied to the face of the sign. Sufficient space shall be left between the covering and the face to permit air flow over the sign.

5 Traffic signs which are to be covered shall not be erected on trafficked highways without the covering in place.

6 Removal of any covering shall be carried out with the minimum disturbance to traffic.

7 Irrespective of any requirement in Appendix 12/1 to cover signs, any traffic sign erected at such a time that its legend does not relate either wholly or in part to the traffic movement and route in operation, shall have its sign face securely covered with one of the materials in sub-Clause 1 of this Clause until such time as its legend is applicable.

1210 Permanent Bollards

1 Permanent bollards shall be as described in Appendix 12/1 and shall comply with appropriate Clauses of this Series.

2 Internally illuminated bollards and, unless otherwise described in Appendix 12/1 reflective-only bollards, shall be secured by stainless steel holding down bolts, nuts and washers. Holding down bolts and anchorages cast into the foundation shall be capable of complying with the performance requirements of BS 873 : Part 3 when tested as described therein.

3 All bolts shall be lightly greased before final installation and tightening to the bollard manufacturer's torque setting.

1211 Permanent Marker Posts

General

1 Permanent marker posts shall be constructed to the

dimensions and be installed in the locations and by methods described in Appendix 12/2 and shall comply with this Series and sub-Clauses 2 and 3 of this Clause.

Distance Marker Posts

2 Distance marker posts shall be made from plastics, timber, or other materials described in Appendix 12/2.

Hazard Marker Posts

3 Hazard marker posts shall comply with BS 873 : Part 2. Post construction and colour and type of reflective marker shall be as described in Appendix 12/2.

#1212 Road Markings

General

1 Road markings shall be white or yellow complying with BS 381C No. 355, as appropriate except where an alternative shade has been specified in Appendix 12/3. They shall consist of continuous or intermittent lines, letters, figures, arrows or symbols and comply with sub-Clauses 2 to 10 of this Clause.

Statutory requirements controlling road markings are contained in the Traffic Signs Regulations and General Directions (Statutory Instrument No. 1519 1994) and subsequent amending Regulations.

Permanent Road Markings

2 Permanent road markings shall be one of the following materials and comply with the colour, location and material type requirements described in Appendix 12/3:

- (i) thermoplastic material complying with BS 3262 : Class A;
- (ii) road marking paint complying with BS 6044;
- (iii) permanent preformed road markings complying with BS 7396;
- (iv) other materials described in Appendix 12/3.

3 For thermoplastic material where the specified average texture depth of the carriageway surface is 1.5 mm or more, the width tolerances and thickness for 'screed', 'sprayed' or extruded white or yellow lines shall be in accordance with BS 3262: Part 3. With the exception of raised rib or profiled markings, in no case shall any material be laid more than 5.0 mm thick. The method of thickness measurement shall be as described

in BS 3262 : Part 3. Where thermoplastic material markings are to be reflectorised, solid glass beads complying with BS 6088 shall be incorporated into the thermoplastic mixture and applied to the wet surface of the material in compliance with BS 3262 : Part 3.

Where there is a requirement for enhanced reflectorised marking materials, large diameter glass beads to produce improved wet night visibility shall be used in accordance with BS 3262 : Part 1. The surface application rate shall be between 500 and 850 g/sq m. The drop-on aggregates shall be as defined in BS 3262: Part 1, in order to ensure that the minimum skid resistance of the marking material is not less than the minimum requirements contained in sub-Clause 5 of this Clause.

4 When laid, the wet film thickness of road marking paint shall be not less than 315 microns and not more than 400 microns, exclusive of surface applied solid glass beads. Road marking paint shall be supplied fresh and ready for use in sealed containers and stored in accordance with the manufacturer's instructions. Where road marking paint requires thinners they shall be used in accordance with the paint manufacturer's recommendations. Where painted road markings are to be reflectorised, solid glass beads shall be applied uniformly on to the wet paint film at the rate of 400-500 g/m². The solid glass beads shall comply with BS 6088.

5 The skid resistance level for road markings measured as described in BS 3262 : Part 1, BS 6044 and BS 7396 shall be not less than 45, except in those locations described in the Appendix 12/3 where a level of not less than 55 is required.

6 The pavement shall be prepared in compliance with BS 3262 : Part 3, and additionally:

- (i) on concrete carriageways the transverse texturing, where the marking is to be applied, shall be freed from all traces of curing compound by wire brushing or other approved means. Prior to the application of the thermoplastic material a tack coat compatible with the road surface and the marking material shall be applied in accordance with the manufacturer's instructions;
- (ii) on surface dressed carriageways, all loose chippings where the marking is to be applied shall be removed prior to application.

7 Road marking materials shall only be applied to surfaces which are clean and dry. Markings shall be free from raggedness at their edges and shall be uniform and free from streaks. Longitudinal road markings shall be laid by mechanical means to a regular alignment.

Raised Rib Road Markings

8 Raised Rib Road Markings shall only be adopted with the prior approval of the Overseeing Organisation and shall only be used on motorways or all-purpose roads (both single and dual carriageway) with at least 1 metre wide hardstrips/hardshoulders. They shall comply with sub-Clauses 1, 2(i), 3, 5, 6 and 7 of this Clause.

9 Raised Rib Road Markings shall be white lines which are continuous over the sections where they are specified in Appendix 12/3. Where specified in Appendix 12/3 gaps shall be provided for drainage purposes.

10 Raised Rib Road markings shall be in accordance with the Traffic Signs Regulations and General Directions 1994 (Statutory Instrument No. 1519 1994), including Diagrams 1012.2 and 1012.3, as appropriate. Spacing of the transverse raised ribs shall be 500 mm or 250 mm as specified in Appendix 12/3.

11 Raised Rib Road Markings shall not be used adjacent to hatched areas or central reserve crossings.

Temporary Road Markings

12 Temporary road markings shall only be adopted with the prior approval of the Overseeing Organisation. They shall either comply with sub-Clauses 1 to 7 of this Clause or if required to be removable, be constructed from a proprietary prefabricated road marking material complying with BSI Published Document PD 6518.

13 When temporary road markings are used on surfaces that will continue to be used by public traffic after their removal, any shadow trace remaining after their removal shall be permanently obliterated. Prefabricated materials shall not be used for this obliteration.

14 Temporary road markings constructed from a proprietary prefabricated road marking material shall only be adopted in locations and on types of road surface as described in Appendix 12/3 and shall comply with any other requirement therein. The marking material shall be new and together with any primer shall be stored and installed in accordance with the manufacturer's instructions and within the recommended shelf life. Prefabricated road markings shall only be applied to surfaces that are clean and dry. Upon removal they shall be disposed of off Site and if any making good is necessary to the road surface it shall be satisfactorily carried out before the road is opened to traffic.

15 Only prefabricated temporary road marking materials which have received type approval in accordance with the requirements of BSI Published Document PD 6518 shall be incorporated into the

Works.

Road Markings on Porous Asphalt Surfacing

16 Spray paint, thermoplastic or preformed road markings shall be used for carriageway markings on porous asphalt surfacing. Manual screeding of road markings shall not be permitted except for directional arrows and similar markings.

Removal of Road Markings

17 The removal of road markings on surfaces that will continue to be used by traffic shall be undertaken in a manner that will avoid damage to the surface.

The removal of temporary road markings shall comply with sub-Clauses 1212.13 and 1212.14.

The removal of permanent road markings shall be by mechanical means only. The Contractor shall submit details of the system he proposes to use to the Overseeing Organisation for approval.

#1213 Road Studs

Reflecting Road Studs

1 Statutory requirements controlling reflecting road studs are contained in the Traffic Signs Regulations and General Directions (Statutory Instrument No. 1519 1994) Regulations 28, 29 and Direction 50 and subsequent amending Regulations.

2 All reflecting road studs shall comply with BS 873: Part 4.

3 Only reflecting road studs and components which have received statutory type approval by the Secretary of State shall be incorporated into the Works. They shall be installed in accordance with the manufacturer's instructions.

4 The Contractor shall submit details of the reflecting road studs he proposes to use in the Works to the Overseeing Organisation for approval.

Permanent Reflecting Road Studs

5 Permanent reflecting road studs shall be installed in the locations and to any other requirements as described in Appendix 12/3.

Temporary Reflecting Road Studs

6 Temporary reflecting road studs shall be one of the fluorescent saturn yellow types and be appropriate for

the situation concerned. They shall not be used for a second application.

Adhesive and tack coat used for the temporary reflecting road studs shall be removed from the carriageway on completion of the Works.

Non-reflecting Road Studs

7 All non-reflecting road studs shall be installed in accordance with the manufacturer's instructions in locations, and complying with any other requirements, described in Appendix 12/3.

Reflecting Road Studs on Porous Asphalt Surfacing

8 The edges of recesses for reflecting road studs in porous asphalt surfacing shall be dry-sawn or milled when the material has cooled to ambient temperature. Care shall be exercised when removing porous asphalt to form the recess to prevent damage occurring to the cut edges and to prevent detritus clogging the porous asphalt surfacing.

1214 Traffic Cones, Traffic Cylinders, Flat Traffic Delineators and Other Traffic Delineators

General

1 Traffic cones and traffic cylinders, hereinafter termed cones and cylinders, shall comply with Designation 1 or Designation 2 of BS 873 : Part 8. Cones shall be to Category A.

2 Flat Traffic Delineators, hereinafter termed FTDs, shall comply with sub-Clauses 3 to 17 of this Clause.

3 A FTD shall comprise a flat blade fixed to a base. The flat blade may incorporate stiffeners provided that they do not encroach into the white retroreflective area.

4 FTDs shall be constructed of rubber or plastic materials. It shall be possible to insert and remove blades without requiring a special tool. The height of the FTD shall be 750 mm or 1000 mm as stated in Appendix 12/4. The width of the top of the blade shall be 45 ± 10 mm. Other dimensions shall be in accordance with Diagram 7102 of TSRGD 1994, or the Traffic Signs Regulations (Northern Ireland) 1997 as appropriate.

5 FTD bases shall be so designed that they will stack without binding and without causing damage to the retroreflective surfaces. Additionally the blades and their attachment to the base or fixing shall be so designed that the blade's face presents throughout its design life a plane to the approaching traffic no more than 12.5° from the vertical.

6 FTD bases may be coloured red, black, grey or brown. They may have a 100 mm wide white reflective line placed on one edge of the base provided:

- (i) the edge of the base where the white line is to be attached comprises a sloping surface which is at an angle to the road surface of no more than 60° and is of such dimensions either to fully accommodate the 100 mm wide white line or, where the angle between the road surface and the sloping surface exceeds 30°, to accommodate at least 80 mm of the width of the white line, the excess (maximum 20 mm) being returned onto the top surface of the base;
- (ii) the material from which the base is manufactured allows proper adhesion or attachment of the white reflective line to prevent it becoming detached during normal use;
- (iii) the coverage of white reflective material is maintained at more than 70% of the area treated.

7 The white reflective strip material shall comply with BS 3262 : Part 1 or BS 6044 as appropriate. Additionally when tested using a portable retroreflectometer the white line shall have a coefficient of retroreflectance of not less than 150 mcd/(lux/m²).

8 FTD blades shall be coloured red and white as indicated in Diagram 7102 of TSRGD 1994, or the Traffic Signs Regulations (Northern Ireland) 1997 as appropriate.

9 The white portions of the FTD blades shall comply with the chromaticity co-ordinates and luminance factor given in BS 873 : Part 6.

10 The red portions of the FTD shall comply with the chromaticity co-ordinates and luminance factor for traffic cones given in BS 873 : Part 8 when measured in accordance with BS 873 : Part 1.

11 That part of the blade coloured white shall comprise retroreflective material, complying with the requirements for Class 1 or Class 2 as specified in BS 873 : Part 6, which shall be securely applied or attached to the blade to prevent it becoming detached during normal use.

12 The red portions may also be retroreflective.

13 The minimum mass of the FTD including any ballast recommended by the manufacturer shall comply with the mass of a traffic cone as defined in BS 873 : Part 8.

14 FTDs shall be clearly and durably marked with the following information in the following order:

- (a) the name, trade mark or other means of identification of the manufacturer or vendor;
- (b) the title and date of this document, ie. Specification for Highway Works, with appropriate date.

The marking shall be in characters legible at a normal reading distance such that the total area of the marking does not exceed 30 cm². Additionally the legend 'DUAL CARRIAGEWAY AND MOTORWAY USE ONLY' shall be applied to the lowermost red portion of the blade, using block capitals of minimum height 15 mm, in such a location that it can be clearly seen when the FTD is in position.

15 All markings shall be sufficiently durable to last the expected life of the FTD to which they are applied and in no case less than five years.

16 When checked by inspection and by rubbing lightly, first for 15 seconds with a piece of cloth soaked in water and then for 15 seconds with a piece of cloth soaked in petroleum spirit, followed by 15 seconds with a piece of cloth soaked in diesel oil, the marking shall still be legible.

17 FTDs shall be supplied with the following information:

- (a) instructions for ballasting (if required);
- (b) instructions for fixing blades to bases.

18 Other traffic delineators hereinafter termed delineators shall be as described in Appendix 12/4.

19 The Contractor shall submit to the Overseeing Organisation a copy of a test certificate confirming that samples of the identical type of cone, cylinder, FTD or delineator as those to be used in the Works and supplied as permanent cones, cylinders, FTDs or delineators under the Contract, have been tested and found to comply with sub-Clauses 1 to 18 of this Clause.

Permanent Cones, Cylinders, FTDs and Other Delineators

20 Where required in Appendix 1/5 the Contractor shall arrange for the tests described in sub-Clauses 22 to 56 of this Clause, for cones, cylinders, FTDs and other delineators, to be carried out at an approved testing laboratory. The numbers to be tested, as given in Appendix 1/5, are to be selected at random from the batch to be supplied under the Contract. Failure of any test will result in rejection of the batch.

Temporary Cones, Cylinders, FTDs and Other Delineators

21 The Contractor shall submit to the Overseeing Organisation certification substantiating that at least 1

in every 500 of any batch of cones, cylinders, FTDs and delineators to be used in the Temporary Works have passed the tests described in sub-Clauses 22 to 56 of this Clause as appropriate.

Testing

22 Cones and cylinders shall be tested in compliance with BS 873 : Part 8.

23 FTDs shall be tested in compliance with sub-Clauses 24 to 55 of this Clause.

24 Test procedures shall be carried out on each size of FTD and each method of attachment between blade and base.

25 When tested in accordance with sub-Clauses 31 to 38 of this Clause with the exception of the white retroreflective material, no part of the FTD shall crack, split or deform.

26 When samples with retroreflective portions attached are tested in accordance with sub-Clauses 31 to 38 of this Clause the coefficient of luminous intensity, R (as defined in Publication CIE No 54; Retroreflection, definition and measurement), after testing shall be not less than 80% of the value previous to the test.

27 When tested in accordance with sub-Clauses 39 to 43 of this Clause, no part of the FTD with the exception of white retroreflective material, shall crack, fracture or split and any ballast or ballast container shall not have become displaced within the base or separated from it. Any ballast container as either an integral part of the base or enclosed within it shall not have been damaged to the extent that ballast is discharged. Caps or bungs to ballast containers shall not have been forced from their sockets or other fixings.

28 When tested in accordance with sub-Clauses 44 to 49 of this Clause, no part of the FTD with the exception of white retroreflective material shall crack, fracture or split. Bases shall remain in contact with the reference surface.

29 When tested in accordance with sub-Clauses 50 to 55 of this Clause, no part of the FTD with the exception of the white retroreflective material shall crack, fracture or split. Bases shall remain in contact with the reference surface.

30 Throughout the tests in sub-Clauses 31 to 38, 44 to 49, and 50 to 55 of this Clause, the blade shall remain fixed in position. On completion of the testing in accordance with sub-Clauses 44 to 49 and 50 to 55 of this Clause the residual deflection of the top of the blade in any horizontal direction, measured 30 seconds to 60 seconds after completion of the tests, shall be not more than 12.5% of the height of the FTD. The height

of the FTD, H , is as measured from the reference surface.

Low Temperature Impact Test

31 The test shall be conducted using a steel ball swung on a pendulum. The apparatus shall be as shown in HCD Drawing Number K3. The steel ball shall have a mass of 0.9 ± 0.045 kg and be suspended by one or two steel pendulum wires of not more than 1 mm diameter so that the pendulum radius is 1750 ± 10 mm. The point of impact shall be vertically beneath the centre of radius of the pendulum and at a height on the specimen of $H/2 \pm 10$ mm where H is the height of an FTD above the reference surface.

32 FTDs shall be fixed to the reference surface using the base.

33 The test shall be carried out on specimens with and without retroreflective portions attached.

34 For samples with retroreflective portions attached, the coefficient of luminous intensity, R , of every such face at an observation angle of 20° and at an entrance angle normal to the face of the blade prior to the conditioning shall be determined; the definitions of observation angle and entrance angle being those given in BS 873 : Part 1.

35 All test samples shall be conditioned for a period of not less than two hours at a temperature of $-16 \pm 2^\circ\text{C}$. Impact testing shall be carried out within 60 seconds after conditioning.

36 Impact shall be made in ambient conditions of not greater than 20°C .

37 Within one hour of impacting, samples shall be immersed with retroreflective portions attached, in water at $20 \pm 5^\circ\text{C}$ for 10 minutes. After draining for 10 minutes the coefficient of luminous intensity, R , shall be measured in accordance with sub-Clause 34 of this Clause.

38 The sample shall be examined and any damage, percentage change in the coefficient of luminous intensity, or any detachment of a blade from its base shall be reported.

Drop Test

39 FTDs requiring the addition of ballast shall be ballasted as instructed by the manufacturer.

40 The FTD shall be conditioned for a period of not less than two hours at a temperature of $32 \pm 2^\circ\text{C}$.

41 Within one minute after conditioning the FTD shall be suspended with its normal vertical axis horizontal (any cap or bung to a ballast container forming an integral part of the FTD shall be positioned uppermost)

and with its lowest part 1500 ± 5 mm above a solid horizontal surface and dropped once vertically from rest onto the solid surface.

42 The test detailed in sub-Clause 41 shall be repeated after conditioning at a temperature of $-16 \pm 2^\circ\text{C}$.

43 Any damage observed shall be reported.

Bending Test

44 The test shall be carried out on specimens with and without retroreflective portions attached.

45 The blade shall be fixed to the base in accordance with the manufacturer's instructions. The blade and its base shall be conditioned for a period of not less than two hours at a temperature of $-16 \pm 2^\circ\text{C}$. Within 1 minute after conditioning, the blade shall be bent over about its base line by applying a force to the face of the blade at a point on its vertical centre line $H/2 \pm 10$ mm from the top, so that the top edge touches the reference surface or a surface coplanar with it as indicated in the HCD Drawing Number K3. H is the height of the FTD. When the top edge of the blade touches the reference surface the bending force shall be removed immediately.

46 From 30 seconds to 60 seconds after completion the maximum residual horizontal deflection of the top of the blade shall be measured from the vertical axis passing through the centre of the base of the blade and perpendicular to the reference surface.

47 The test shall be repeated in the opposite direction.

48 The procedure in sub-Clauses 45 to 47 of this Clause shall be repeated at a temperature of $32 \pm 2^\circ\text{C}$.

49 The deflections, any damage observed, any detachment of the blade from its base, and any movement of the base shall be reported.

Fatigue Test

50 The test shall be carried out on specimens with and without retroreflective portions attached. This test is to be carried out on a different specimen to that or those tested in sub-Clauses 31 to 38 and 44 to 49 of this Clause.

51 The blade shall be fixed to the base in accordance with the manufacturer's instructions. The test shall be carried out after conditioning the blade and its base for a period of not less than two hours at a temperature of $-16 \pm 2^\circ\text{C}$.

52 By applying a force to the face of blade at a point on its vertical centre line $H/2 \pm 10$ mm from the top, the top of the blade shall be oscillated as indicated in the HCD Drawing Number K3 at a frequency of 60

oscillations per minute to 90 oscillations per minute at an amplitude of $H/4$ for 10 minutes with the reference surface held in a horizontal position. H is the height of the FTD. One oscillation is the movement from the upright position to the maximum amplitude in one direction, then to the maximum amplitude in the opposite direction and then the return to the upright position.

53 From 30 seconds to 60 seconds after completion the maximum residual horizontal deflection of the top of the blade shall be measured from the vertical axis passing through the centre of the base of the blade and perpendicular to the reference surface.

54 The procedure in sub-Clauses 51 to 53 of this Clause shall be repeated at a temperature of $32 \pm 2^\circ\text{C}$.

55 The deflection, any damage observed and any detachment of the blade from its base shall be reported.

56 Other traffic delineators shall be tested in compliance with Appendix 12/4.

1215 Road Danger Lamps and High Intensity Flashing Beacons

1 Road danger lamps and high intensity flashing beacons shall be used in accordance with Regulations 43 and 42 respectively of TSRGD 1994, or Regulations 44 and 43 respectively of the Traffic Signs Regulations (Northern Ireland) 1997 as appropriate, and shall comply with BS 3143.

1216 Temporary Traffic Signs

1 Temporary traffic signs shall be designed by the Contractor, comply with Clause 1201, satisfy Clause 117, have the consent of the Overseeing Organisation prior to installation, and comply with sub-Clauses 2 to 6 of this Clause.

Temporary traffic signs shall comply with the Traffic Signs Regulations and General Directions 1994, or the Traffic Signs Regulations (Northern Ireland) 1997 as appropriate, and be designed in accordance with Working Drawings for Traffic Sign Design and Manufacture (Volume 3) and where appropriate Local Transport Notes 1/94 and 2/94, and relevant chapters of the Traffic Signs Manual.

2 Temporary traffic signs shall be constructed as follows:

- (i) plate signs and internally illuminated signs:
 - (a) the coefficient of retroreflection of the material for the faces of signs used for Type A or Type B works, as defined in Chapter 8 of the Traffic Signs Manual,

and any amendment thereto including the amendments specified in sub-Clause 117.8, shall be as given in BS 873: Part 6 for Class 1 material;

- (b) where the sign is to be erected for less than six months, it shall, unless Appendix 12/1 requires it to be constructed to a similar standard as a permanent sign, be either a portable sign complying with BS 873 : Part 2 or a fixed short life sign complying with sub-Clause 3 of this Clause;
 - (c) where the sign is to be erected for periods of six months or more, or where Appendix 12/1 requires it to be constructed to the standard for a permanent sign, it shall comply with the requirements for permanent traffic signs;
 - (d) in addition to either (b) or (c) above, electrical work related to temporary traffic signs shall comply with the 1400 Series except Clauses 1402, 1410 and 1425;
- (ii) bollards and marker posts shall comply with Clauses 1210 and 1211;
- (iii) road studs:
- (a) temporary reflecting road studs shall comply with Clause 1213 and only be installed for periods of up to three months and thereupon be replaced;
 - (b) if permanent reflecting road studs are used for temporary purposes they shall comply with Clause 1213 and have the prior approval of the Overseeing Organisation;
- (iv) road markings, cones, cylinders and delineators, road danger lamps and high intensity flashing beacons shall comply with Clauses 1212, 1214 and 1215 as appropriate;
- (v) portable traffic signals and haul route crossing signals shall, where relevant, comply with Clause 1217;
- (vi) any other signal, lamp, barrier or device shall be suitable for its intended purpose and where relevant shall comply with appropriate British Standards.

3 Fixed short life signs shall be constructed as follows:

- (i) materials:
 - (a) sign plates may be constructed of

materials to the standard for a permanent sign, or alternatively shall be constructed of timber, hardboard, plywood or chipboard;

- (b) stiffening frames for sign plates constructed of timber, hardboard, plywood or chipboard, shall be constructed of timber, mild steel or aluminium sections;
 - (c) mounting posts shall be constructed of steel, cast iron, aluminium alloy, reinforced or prestressed concrete or timber;
 - (d) fittings for signs made of materials to the standard for a permanent sign, shall be similar to those used for permanent signs. For signs made of timber, hardboard, plywood or chipboard, fittings shall be of steel, stainless steel, or brass wood screws, or wire nails. Adhesives may be used for fixing provided they are weatherproof and are not affected by variations in temperature;
 - (e) sign plates constructed of timber, hardboard, plywood or chipboard shall be sealed or otherwise treated to ensure that the final finish will provide a satisfactory appearance and will not deteriorate during the period the sign is expected to be in use;
- (ii) construction:
- (a) sign plates shall be constructed on similar principles to those required for permanent signs, although stiffening may be omitted provided the sign plate passes the bending test given in BS 873: Part 1;
 - (b) stiffening frames constructed of timber members shall be jointed so that they withstand adverse weather conditions;
 - (c) mounting posts constructed of timber shall have dimensions that are sufficient to withstand the estimated loading on the sign;
 - (d) fixing of signs to the stiffening frame where required, and to the mounting posts shall be by screwing, nailing or gluing;
 - (e) timber sign plates, stiffening frames and mounting posts shall be preserved with copper/chrome/arsenic (CCA) complying with BS 4072. The sign plate face shall be finished to comply with BS 873 : Part 6.

- 4 Erection of temporary traffic signs mounted on posts shall comply with Clause 1208.
- 5 Any temporary covering of temporary traffic signs shall comply with Clause 1209. Any temporary covering of road studs and road markings shall comply with any requirements described in Appendix 12/3.
- 6 Removal of temporary traffic signs shall be carried out as soon as they become superfluous or a hazard to traffic. Methods of removal shall ensure the minimum disturbance to traffic consistent with safety. Making good shall be carried out immediately after removal of the traffic sign.
- 7 Posts shall not protrude above the top of the sign unless supporting an external luminaire, in which case the protrusion shall be kept to a minimum.

1217 Traffic Signals

General

- 1 Traffic signals shall comprise road junction signals, pelican and puffin pedestrian crossing signals, haul route signals and wig-wag signals and shall be of the type described in Appendix 12/5.
- 2 Traffic signals shall comply with sub-Clauses 3 to 15 of this Clause and the requirements described in Appendix 12/5.
- 3 Traffic signal equipment shall comply with BS 505 : 1971 (AMD 1990, 1976) as amended by Specification TR 0102. It shall consist of control equipment including detector loops of a type which has received statutory type approval by the Secretary of State in accordance with the procedure described in Specification TRG 0500. They shall be maintained and serviced as described in Appendix 12/5.
- 4 All traffic safety and management measures associated with work on traffic signals shall comply with Clause 117, and any work entailing the switching off of existing signals shall not be carried out until the highway authority has been informed and until agreed alternative traffic management measures are in operation to safeguard and control vehicles using the highway.

Controllers

- 5 Controllers shall be provided and installed as described in Appendix 12/5. The cabinet shall be mounted on a foundation, with or without an adjacent inspection chamber as described in Appendix 12/5. The foundation shall make provision for the entry of the appropriate number of cable ducts.

- 6 Traffic signal controllers shall, in addition to any testing carried out in compliance with Clause 1424 be tested before delivery to Site and again after installation but before commissioning, to ensure they comply with the specification in Appendix 12/5.

Cabling and Electrical Requirements

- 7 Traffic signal equipment on each post shall be connected to the controller in accordance with the requirements described in Appendix 12/5.
- 8 The installation shall comply with BS 7671 Regulations for Electrical Installations (IEE Wiring Regulations) and the rules and regulations of the electricity supplier which provides the supply.
- 9 Cables shall be PVC insulated and sheathed 600/1000 V grade with steel wire armouring to BS 6346 and shall be installed in ducts in compliance with Clause 1421 and terminated in compliance with Clause 1423. Reinstatement shall be in compliance with Clause 706.
- 10 Earthing of all posts, pushbutton boxes and the controller cabinet shall comply with Clause 1420. One conductor in each cable between a post and the equipment cabinet shall be a protective conductor and shall bond the earth terminal at the post to the main earth terminal.
- 11 Cable testing shall be in accordance with Clause 1424. Tests (a), (b), (c), (e), (f), (g), (h) and (j) as defined in sub-Clause 1424.2 shall be conducted and all measurements recorded.

Telecommunications Carrier Interface

- 12 Where a connection interface to the plant of a telecommunications carrier is specified in Appendix 12/5 the installation shall comply with the rules and regulations of that carrier.

Posts

- 13 Posts for traffic signals shall be installed in compliance with Clause 1203 and in the locations specified in Appendix 12/5.

Signal Heads

- 14 All backing boards shall have a border of Class 1 retroreflective material (white). Pressure sensitive material shall normally be supplied but vacuum applied material may be used in accordance with the manufacturer's process. Application of pressure sensitive material shall take place only on dry surfaces. An ambient temperature of 15°C minimum is recommended for satisfactory adhesion. The material shall have a 50 mm width throughout. Where the

continuous border bridges each backing board/signal head a distinct cut edge shall be made to avoid any subsequent stretching/ shrinkage of dissimilar surfaces. The finished border shall be of a neat appearance and not made up of short lengths of cuttings.

Road Markings

15 Road markings associated with traffic signals shall comply with Clause 1212.

1218 Detector Loops

1 The installation and testing of detector loops shall be in accordance with Specification MCH 1540.

1219 Controlled and Un-controlled Crossings

1 The location of controlled and un-controlled crossings shall be as described in Appendix 12/5. Details shall be as described in Appendix 12/5.

2 Surfacing of Zebra crossing areas shall be laid with materials and to methods specified in Appendix 12/5. The finished surfacing shall have a minimum skid resistance value of 55 when tested in compliance with:

- (i) BS 3262 : Part 1 for thermoplastic material and prefabricated tiles; or
- (ii) BS 6044 for paint.

3 Non-reflecting road studs shall comply with Clause 1213.

4 Road markings shall be white and comply with Clause 1212 for permanent markings and be of the material described in Appendix 12/5.

5 Traffic signals, related control and other equipment where incorporated in controlled crossings together with installation and reinstatement shall comply with Clause 1217 for permanent traffic signals.

1220 Traffic Signs on Gantries

1 Where traffic signs (including signals) are erected on gantries the signs shall comply with the requirements of the relevant clauses of this Series.

2 Fabricated steel gantries shall be constructed to the requirements described in Appendix 12/6, and to comply with the 1800 Series. Reinforced or prestressed concrete gantries shall be as described in Appendix 12/6 and shall comply with the 1700 Series.

1221 Preparation and Finish of Metal and Other Surfaces

General

1 Permanent traffic signs and, where specified in Appendix 12/1 prescribed temporary traffic signs shall be prepared, protected against corrosion and finished in compliance with BS 873 : Part 6 and with sub-Clauses 2 to 9 of this Clause.

Faces

2 Faces of sign plates shall be prepared to receive sign face materials in compliance with BS 873 : Part 6 and to the recommendations of the sign face material manufacturer following completion of any preparation and finish in sub-Clauses 3 and 6 of this Clause.

Steel Sign Plates, Purlins, Frames and Fittings

3 Steel sign plates, frames and fittings and purlins shall be prepared and protected in compliance with BS 873 : Part 6 and be as described in Appendix 12/1. Preparation to clean steel 2nd Quality and painting of surfaces shall comply with the 1900 Series.

Steel Posts and Post Housings

4 Steel posts and post housings shall be prepared and protected in compliance with BS 873 : Part 7. Painting shall comply with the 1900 Series and be as described in Appendix 19/4.

Aluminium or Aluminium Alloy Posts and Post Housings

5 Aluminium or aluminium alloy posts and post housings shall, unless otherwise required in Appendix 19/4, be left unpainted, except for the bituminous coating required by BS 873 : Part 7 below ground level. A matt appearance shall be achieved in accordance with sub-Clause 6(ii) of this Clause.

Aluminium or Aluminium Alloy Sign Plates, Framework and Stiffening and Luminaire Housings

6 Backs of aluminium or aluminium alloy sheet and planks forming plate signs and external parts of luminaire housings and other permanently exposed components shall, to prevent specular reflection, be dulled using a method to be agreed by the Overseeing Organisation or be coated with either paint or plastics as follows:

- (i) plastics coating, and pre-treatment before its application, shall be in compliance with BS 873 : Part 6;

- (ii) surfaces to be painted shall be lightly abraded in accordance with sub-Clauses 1903.5 and 1903.6 or degreased and etch primed with primer detailed in Standard BD35, Item No 7. Except for etch primed surfaces, all surfaces shall be immediately cleaned in accordance with sub-Clause 1903.9. All surfaces, including etch primed surfaces, shall be applied with one coat of matt polyurethane paint to Standard BD35, Item No. 168, and colour as described in Appendix 19/4. The paint application shall comply with the appropriate recoat times (over etch primer) as detailed in the paint manufacturer's data sheet and Clauses in 1900 Series.

Internally Housed Electrical Components and Ancillary Equipment

7 Ferrous steel shall be finished inside and out by galvanizing, electro-plating or zinc or aluminium spray all in accordance with the 1900 Series, or other equivalent preparation and finish. Aluminium and other metals shall unless otherwise required in Appendix 14/4 be left untreated.

Stainless Steel Components

8 Unless otherwise required in Appendix 19/4 stainless steel shall be left untreated except where the component is visible against the sign face when it shall be covered by a suitable material, of a colour to match that part of the face.

Cast Iron and Cast Steel Components

9 External surfaces shall be prepared and protected as described in Appendix 19/4. Cabinets and feeder pillars shall have final coats of paint applied on Site after final installation including the fitting of any internal apparatus required as part of the Permanent Works. Internal surfaces shall unless otherwise specified in Appendix 19/4 receive the same treatment as for external surfaces except that final paint coats shall be applied before internal components are installed.

NATIONAL ALTERATIONS OF THE OVERSEEING ORGANISATION OF WALES

1201 WO Regulations, Sign Classification and Standards

Regulations

1 Subject to paragraphs 2 and 3 below, all traffic signs used (including reflectors and road markings), whether permanent or temporary, shall be of the size, shape, colour and type prescribed for that use in the Traffic Signs Regulations and General Directions (Statutory Instrument No. 1519 1994), the Traffic Signs (Welsh and English Language Provisions) Regulations, the Zebra, Pelican and Puffin Pedestrian Crossings Regulations and General Directions (Statutory Instrument No. 2400 1997) and subsequent amending Regulations. Other relevant requirements are contained in the above Regulations and General Directions, apart from bilingual sign layouts which shall be as stated in Appendix 12/1.

2 Signs that are not prescribed in Regulations need to be specially authorised by the Secretary of State. Where the Contractor proposes to use non-prescribed temporary traffic signs, he shall obtain the agreement of the Overseeing Organisation to their intended design and location. Where the Contractor proposes to use prescribed temporary traffic signs, he shall obtain the agreement of the police and the highway authority to their intended location. The Contractor shall obtain authorisation and approval from the Overseeing Organisation for the use of the signs at the specific locations proposed.

3 Signs that are changeable by means other than the purely mechanical require statutory type approval for their construction and operating mechanisms by the Secretary of State. This requirement is in addition to the need for the design of the sign to be prescribed or specially authorised. The Contractor's proposal for signs that require statutory type approval shall include the reference numbers of any approval already issued in respect of that equipment. The signs shall not be installed until appropriate approval or confirmation of existing approval, by the Overseeing Organisation has been obtained.

Sign Classification

4 For the purposes of the Contract the following classifications apply:

- (i) permanent traffic signs. Any of the traffic

signs prescribed in the Regulations, or specially authorised by the Secretary of State, or any part thereof, designed to remain in position at the completion of the Permanent Works or a traffic cone, cylinder or other traffic delineator to be retained by the Employer;

- (ii) prescribed temporary traffic signs. Any of the traffic signs defined in the Regulations, or specially authorised by the Secretary of State, or any part thereof, described in Appendix 12/1 which, unless otherwise described in Appendix 12/1, comply with the requirements of a permanent traffic sign but which will not remain in position at the completion of the Permanent Works;

- (iii) temporary traffic signs. Any of the traffic signs defined in the Regulations, or specially authorised by the Secretary of State, or any part thereof, designed by the Contractor, in compliance with Clause 1216 which will not remain in position at the completion of the Permanent Works.

Standards

5 Traffic signs shall comply with BS 873 : Parts 1 to 8 unless otherwise stated.

NATIONAL ALTERATIONS OF THE OVERSEEING ORGANISATION OF NORTHERN IRELAND

1201NI Regulations, Sign Classification and Standards

1 All traffic signs whether Permanent, Prescribed Temporary, or Temporary shall be the size, shape, colour and type prescribed in and be installed in compliance with the requirements of the Traffic Signs Regulations (Northern Ireland) 1997, the 'Zebra' Pedestrian Crossings Regulations (Northern Ireland) 1974, the 'Pelican' Pedestrian Crossings Regulations (Northern Ireland) 1989, and subsequent amending Regulations, or as specifically authorised for use by the Overseeing Organisation.

2 Signs that are changeable by means other than the purely mechanical require type approval by the Overseeing Organisation. This requirement is in addition to the need for the design of the sign to be prescribed. The Contractor's proposal for signs that require type approval shall include the reference numbers of any approval already issued in respect of that equipment. The signs shall not be installed until appropriate approval or confirmation of existing approval, by the Overseeing Organisation has been obtained.

Sign Classification

- 3 For the purpose of the Contract the following classifications apply:
- permanent traffic signs. Any of the traffic signs prescribed in the Regulations, or any part thereof, designed to remain in position at the completion of the Permanent Works or a traffic cone, cylinder or other traffic delineator to be retained by the Employer;
 - prescribed temporary traffic signs. Any of the traffic signs defined in the Regulations, or any part thereof, described in Appendix 12/1 which, unless otherwise described in Appendix 12/1, comply with the requirements of a permanent traffic sign but which will not remain in position at the completion of the Permanent Works;
 - temporary traffic signs. Any of the traffic signs defined in the Regulations, or any part thereof, designed by the Contractor in compliance with Clause 1216 which will not remain in position at the completion of the Permanent Works.

Standards

4 Traffic signs shall comply with BS 873: Parts 1 to 8 unless otherwise stated.

1212NI Road Markings

General

1 Road markings shall be white or yellow complying with BS 381C No. 355, as appropriate except where an alternative shade has been specified in Appendix 12/3. They shall consist of continuous or intermittent lines, letters, figures, arrows or symbols and comply with sub-Clauses 2 to 10 of this Clause.

Statutory requirements controlling road markings are contained in the Traffic Signs Regulations (Northern Ireland) 1997 and subsequent amending Regulations.

Permanent Road Markings

- 2 Permanent road markings shall be one of the following materials and comply with the colour, location and material type requirements described in Appendix 12/3:
- thermoplastic material complying with BS 3262: Class A;
 - road marking paint complying with BS 6044;
 - permanent preformed road markings complying with BS 7396;
 - other materials described in Appendix 12/3.
- 3 For thermoplastic material where the specified average texture depth of the carriageway surface is 1.5 mm or more, the thickness for 'screed', 'sprayed' or 'extruded' white or yellow lines shall be in accordance with BS 3262: Part 3. With the exception of raised rib or profiled markings, in no case shall any material be laid more than 5.0 mm thick. The method of thickness measurement shall be as described in BS 3262 : Part 3. Where thermoplastic material markings are to be reflectorised, solid glass beads complying with BS 6088 shall be incorporated into the thermoplastic mixture and applied to the wet surface of the material in compliance with BS 3262 : Part 3.

Where there is a requirement for enhanced reflectorised marking materials, large diameter glass beads to produce improved wet night visibility shall be used in accordance with BS3262 : Part 1. The surface application rate shall be between 500 and 850 g/sq m. The drop-on aggregates shall be as defined in BS 3262: Part 1, in order to ensure that the minimum skid resistance of the marking material is not less than the minimum requirements contained in sub-Clause 5 of this Clause.

4 When laid, the wet film thickness of road marking paint shall be not less than 315 microns and not more than 400 microns, exclusive of surface applied solid glass beads. Road marking paint shall be supplied fresh and ready for use in sealed containers and stored in accordance with the manufacturer's instructions. Where road marking paint requires thinners they shall be used in accordance with the paint manufacturer's recommendations. Where painted road markings are to be reflectorised, solid glass beads shall be applied uniformly on to the wet paint film at the rate of 400-500 g/m². The solid glass beads shall comply with BS 6088.

5 The skid resistance level for road markings measured as described in BS 3262 : Part 1, BS 6044 and BS 7396 shall be not less than 45, except in those locations described in the Appendix 12/3 where a level of not less than 55 is required.

6 The pavement shall be prepared in compliance with BS 3262 : Part 3, and additionally:

- (i) on concrete carriageways the transverse texturing, where the marking is to be applied, shall be freed from all traces of curing compound by wire brushing or other approved means. Prior to the application of the thermoplastic material a tack coat compatible with the road surface and the marking material shall be applied in accordance with the manufacturer's instructions;
- (ii) on surface dressed carriageways, all loose chippings where the marking is to be applied shall be removed prior to application.

7 Road marking materials shall only be applied to surfaces which are clean and dry. Markings shall be free from raggedness at their edges and shall be uniform and free from streaks. Longitudinal road markings shall be laid by mechanical means to a regular alignment.

Raised Rib Road Markings

8 Raised Rib Road Markings shall only be adopted with the prior approval of the Overseeing Organisation and shall only be used on motorways or all purpose roads (both single and dual carriageway) with at least 1

metre wide hardstrips/hardshoulders. They shall comply with sub-Clauses 1, 2(i), 3, 5, 6 and 7 of this Clause.

9 Raised Rib Road Markings shall be white lines which are continuous over the sections where they are specified in Appendix 12/3. Where specified in Appendix 12/3 gaps shall be provided for drainage purposes.

10 Raised Rib Road Markings shall be in accordance with the Traffic Signs Regulations (Northern Ireland) 1997, including Diagrams 1012.2 and 1012.3, as appropriate. Spacing of the transverse raised ribs shall be 500 mm or 250 mm as specified in Appendix 12/3. The transverse raised ribs shall not be less than 40 mm nor more than 50 mm long in the direction of travel and they need not be continuous over the width of the specified line but shall not be less than 80% of this width.

11 Raised Rib Road Markings shall not be used adjacent to hatched areas or central reserve crossings.

Temporary Road Markings

12 Temporary road markings shall only be adopted with the prior approval of the Overseeing Organisation. They shall either comply with sub-Clauses 1 to 7 of this Clause or if required to be removable, be constructed from a proprietary prefabricated road marking material complying with BSI Published Document PD 6518.

13 When temporary road markings are used on surfaces that will continue to be used by public traffic after their removal, any shadow trace remaining after their removal shall be permanently obliterated. Prefabricated materials shall not be used for this obliteration.

14 Temporary road markings constructed from a proprietary prefabricated road marking material shall only be adopted in locations and on types of road surface as described in Appendix 12/3 and shall comply with any other requirement therein. The marking material shall be new and together with any primer shall be stored and installed in accordance with the manufacturer's instructions and within the recommended shelf life. Prefabricated road markings shall only be applied to surfaces that are clean and dry. Upon removal they shall be disposed of off Site and if any making good is necessary to the road surface it shall be satisfactorily carried out before the road is opened to traffic.

15 Only prefabricated temporary road marking materials which have received type approval in accordance with the requirements of BSI Published Document PD 6518 shall be incorporated into the Works.

Road Markings on Porous Asphalt Surfacing

16 Spray paint, thermoplastic or preformed road markings shall be used for carriageway markings on porous asphalt surfacing. Manual screeding of road markings shall not be permitted except for directional arrows and similar markings

Removal of Road Markings

17 The removal of road markings on surfaces that will continue to be used by traffic shall be undertaken in a manner that will avoid damage to the surface.

The removal of temporary road markings shall comply with sub-Clauses 1212.13 and 1212.14.

The removal of permanent road markings shall be by mechanical means only. The Contractor shall submit details of the system he proposes to use to the Overseeing Organisation for approval.

1213NI Road Studs

Reflecting Road Studs

1 Statutory requirements controlling reflecting road studs are contained in the Traffic Signs Regulations (Northern Ireland) 1997 and subsequent amending Regulations.

2 All reflecting road studs shall comply with BS 873 : Part 4.

3 Only reflecting road studs which have received type approval of the Overseeing Organisation shall be incorporated into the Works. They shall be installed in accordance with the manufacturer's instructions.

4 The Contractor shall submit details of the reflecting road studs he proposes to use in the Works to the Overseeing Organisation for approval.

Permanent Reflecting Road Studs

5 Permanent reflecting road studs shall be installed in the locations and to any other requirements as described in Appendix 12/3.

Temporary Reflecting Road Studs

6 Temporary reflecting road studs shall be one of the fluorescent saturn yellow types and be appropriate for the situation concerned. They shall not be used for a second application.

Adhesive and tack coat used for the temporary reflecting road studs shall be removed from the carriageway on completion of the Works.

Non-reflecting Road Studs

7 All non-reflecting road studs shall be installed in accordance with the manufacturer's instructions in locations, and complying with any other requirements, described in Appendix 12/3.

Reflecting Road Studs on Porous Asphalt Surfacing

8 The edges of recesses for reflecting road studs in porous asphalt surfacing shall be dry-sawn or milled when the material has cooled to ambient temperature. Care shall be exercised when removing porous asphalt to form the recess to prevent damage occurring to the cut edges and to prevent detritus clogging the porous asphalt surfacing.